

100mm Axial Fan with Humidistat and Pull Cord



[Operations & Maintenance Manual \(pdf\)](#)

[Web Page \(pdf\)](#)

Model: 459294

Axial extract fan with integral humidity timer and a direct switching override at low humidity. The factory setting is 75%RH at a normal 20⁰c but the humidity setting is adjustable between 60%RH to 90%RH

Key Features

- High quality ABS mouldings
- With external gloss finish
- Quiet Operation

Technical Specification

- Meets the requirements of Building Regulation Document F.
- IP44 rated, BEAB Approved, and CE marked in accordance with all the relevant EEC Harmonised Directives.
- Double Insulated, class II motor fitted with thermal protection

- Hole Diameters: Window 105mm, Wall 115mm
- Airflow: Panel Mount 88m³/hr, Window/Wall 69m³/hr

Product Range Details

- Rated Voltage 220-240v-50Hz
- Rated Wattage 16W
- Motor speed 2100rpm
- Noise Level 30dB(A)

Accessories

- Window Kit
- Wall Kit
- External wall grille
- External gravity wall grille
- External gravity grille
- Ducting

Dimensions

Height

-

154mm

Width

-

154mm

Depth

-

47mm

Source URL:

<http://www.anda.co.uk/products/ventilation/100mm-axial-fan-humidistat-and-pull-cord>