

## 100mm Centrifugal Fan with Timer Part L Compliant



Download



[Operations & Maintenance Manual \(pdf\)](#)

[Web Page \(pdf\)](#)

**Model: 401078**

100mm standard centrifugal fan with adjustable electronic overrun timer (1–20 minutes). Suitable for use in toilets, cloakrooms, bathrooms and shower rooms.

### Key Features

- Wall or Ceiling Mounting
- Suitable for wall or ceiling mounting
- High Impact ABS mouldings with external gloss finish
- Integral Backdraught Shutter
- Long Life Motor
- Flush or Surface Mountable
- Adjustable 98mm rear or side exit spigot

### Technical Specification

- Meets the requirements of Building Regulation Document F
- IP44 rated, BEAB Approved, and CE marked in accordance with all the relevant EEC

## Harmonised Directives

- Double Insulated, class II motor fitted with thermal protection
- Hole Diameters: Wall 117mm
- Airflow: 75m<sup>3</sup>/hr

## Product Range Details

- Rated Voltage 220-240v-50Hz
- Rated Wattage 11W
- Noise Level 36dB(A)

## Accessories

- Wall Kit
- External wall grille
- Flexible Ducting

## Dimensions

Height

-

256mm

Width

-

210mm

Depth

-

100mm

## Source URL:

<http://www.anda.co.uk/products/ventilation/100mm-centrifugal-fan-timer-part-l-compliant>