

100mm Humidistat Axial Fan Part L Compliant



Download



[Operations & Maintenance Manual \(pdf\)](#)

[Web Page \(pdf\)](#)

Model: 446675

100mm axial extract fan with Humidity control which is adjustable between 40%RH and 95%RH complete with adjustable timer (1-20 mins) designed to meet the new Part L building regulations, for use in bathrooms and toilets.

Key Features

- SFP down 0.42W/l/s
- Suitable for wall or ceiling mounting
- High Quality ABS moulding with external gloss finish
- Quiet Operation
- Comes complete with backdraught shutter

Technical Specification

- Meets the requirements of Building Regulation Document F and L
- IP44 rated and CE marked in accordance with all the relevant EEC Harmonised Directives

- Double Insulated, class II motor fitted with thermal protection
- Airflow: 91.8m³/hr

Specific Fan Power (SFP) Requirements

Mechanical ventilation systems should be designed to minimise electric fan power. Specific fan power (SFP) should not be worse than:

- i. 0.5 Watts per litres per seconds for intermittent extract ventilation systems
- ii. 0.7 Watts per litres per seconds for continuous extract ventilation systems
- iii. 1.5 Watts per litres per seconds for continuous supply and extract with heat recovery ventilation systems

Product Range Details

- Rated Voltage 220-240v-50Hz
- Rated Wattage 10.77W
- Motor speed 2400rpm
- Noise Level 41dB(A)
- Max. Operating Temp. 40°C
- Max. Pressure 20p.a.

Dimensions

Height

-

205mm

Width

-

205mm

Depth

-

110mm

Source URL:

<http://www.anda.co.uk/products/ventilation/100mm-humidistat-axial-fan-part-l-compliant>