

100mm Low Profile Axial Fan with Timer and Backdraught Shutter



[Operations & Maintenance Manual \(pdf\)](#)

[Web Page \(pdf\)](#)

Model: 459302

Slim axial extract fan with backdraught shutter and electronic overrun timer adjustable from 3 minute to 25 minutes, the factory setting is 15 minutes. Suitable for panel mounting or wall mounting using the appropriate accessory kit.

Key Features

- Slim - only 15mm thick
- Suitable for wall or ceiling mounting
- High Quality ABS mouldings with external gloss finish
- Quiet Operation

Technical Specification

Meets the requirements of Building Regulation Document F.
IP44 rated, BEAB Approved, and CE marked in accordance with all the relevant EEC Harmonised Directives.

Double Insulated, class II motor fitted with thermal protection

Hole Diameters: Wall 115mm

Airflow: Panel Mount 90m³/hr

Product Range Details

Rated Voltage 220-240v-50Hz

Rated Wattage 16W

Noise Level 37.8dB(A)

Accessories

- Window Kit
- Wall Kit
- External wall grille
- External gravity grille
- Ducting

Dimensions

Height

-

159mm

Width

-

159mm

Depth

-

15mm

Source URL:

<http://www.anda.co.uk/products/ventilation/100mm-low-profile-axial-fan-timer-and-backdraught-shutter>