

100mm SELV Low Profile Axial Fan with Timer and Backdraught Shutter



[Operations & Maintenance Manual \(pdf\)](#)

[Web Page \(pdf\)](#)

Model: 405677

Slim axial extract fan with backdraught shutter and electronic overrun timer adjustable from 1 minute to 30 minutes, the factory setting is 15 minutes. SELV 12V AC. Suitable for panel mounting or wall mounting by using the appropriate accessory kit.

Key Features

- SELV (Safety Extra Low Voltage)
- Slim - only 15mm thick
- Suitable for wall or ceiling mounting
- High Quality ABS mouldings with external gloss finish
- Quiet Operation
- Adjustable overrun timer
- Backdraught shutter

Technical Specification

- Meets the installed performance requirements of Building Regulations Document F for a wall fan
- IPX7 fan suitable for installing in zone 1. GS approved and CE marked in accordance with all the relevant EEC Harmonised Directives
- Double Insulated, class III motor fitted with thermal protection, controller class II
- Hole Diameters: Ø115mm
- Airflow: Panel Mount 90m³/hr

Product Range Details

- Rated Voltage 220-240v-50Hz
- Rated Wattage 23W
- Noise Level 37.8dB(A)

Accessories

- Wall Kit
- External wall grille
- External gravity grille
- Ducting

SELV Transformer Dimensions

Height: 86mm
Width: 147mm
Depth: 66mm

Dimensions

Height

-

159mm

Width

-

159mm

Depth

-

15mm

Source URL:

<http://www.anda.co.uk/products/ventilation/100mm-selv-low-profile-axial-fan-timer-and-backdraught-shutter>