

## 100mm Shower Fan and Light Kit with Timer Part L



Download



[Operations & Maintenance Manual \(pdf\)](#)

[Web Page \(pdf\)](#)

**Model: 446681**

100mm timer in line fan shower fan and light kit designed for the safe ventilation of bathrooms, toilets and shower rooms by removing any risk of an electric shock in wet areas as the fan is mounted remotely.

### Key Features

- SFP down to 0.43W/l/s
- Incorporates an integral adjustable electronic timer (1-20 mins)
- Quiet Operation
- Limited to 1.5mtrs of ducting when connected to an axial fan

### Technical Specification

Meets the requirements of Building Regulation Document F and L.

IP44 rated.

CE marked in accordance with all the relevant EEC Harmonised Directives.

Double Insulated, class II

t: 01293 441690 e: [info@anda.co.uk](mailto:info@anda.co.uk) | [sales@anda.co.uk](mailto:sales@anda.co.uk) | [Privacy & Cookies Policy](#)

Motor fitted with thermal protection  
Airflow: Maximum 24 lts/sec

### **Specific Fan Power (SFP) Requirements**

1.0 a. Mechanical ventilation systems should be designed to minimise electric fan

Fan Power power. Specific fan power (SFP) should not be worse than:

- i. 0.5 Watts per litres per seconds for intermittent extract ventilation systems
- ii. 0.7 Watts per litres per seconds for continuous extract ventilation systems
- iii. 1.5 Watts per litres per seconds for continuous supply and extract with heat recovery ventilation systems

### **Product Range Details**

Rated Voltage 220-240v-50Hz  
Maximum Pressure – 20Pa  
Rated Wattage- 10.4watts  
Sound Volume- 41dB(A)  
Max Operating Temp – 40deg.C

### **Source URL:**

<http://www.anda.co.uk/products/ventilation/100mm-shower-fan-and-light-kit-timer-part-l>