

100mm Slim Axial Fan with Chrome Grille Timer and Backdraught Shutter



[Operations & Maintenance Manual \(pdf\)](#)

[Web Page \(pdf\)](#)

Model: 438200

Slim axial extract fan with backdraught shutter and electronic overrun timer adjustable from 3 minute to 25 minutes, the factory setting is 15 minutes. Suitable for panel mounting or wall mounting using the appropriate accessory kit.

Key Features

- Slim – only 15mm thick
- Wall or ceiling mounting
- High quality ABS mouldings
- With external gloss finish
- Quiet Operation

Technical Specification

Meets the requirements of Building Regulation Document F.
IP44 rated, GS Approved, and CE marked

in accordance with all the relevant EEC Harmonised Directives.
Double Insulated, class II motor fitted with Thermal Protection.
Hole Diameters: Wall 115mm
Airflow: Panel Mount 903m/hr
Sound: 37.8dBA @ 3m

Product Range Details

Rated Voltage 220-240v-50Hz
Rated Wattage 16w

Dimensions

Height

-

159

Width

-

159

Depth

-

78mm spigot depth

Source URL:

<http://www.anda.co.uk/products/ventilation/100mm-slim-axial-fan-chrome-grille-timer-and-backdraught-shutter>