

150mm Axial Fan Part L Compliant



[Operations & Maintenance Manual \(pdf\)](#)

[Web Page \(pdf\)](#)

Model: 446676

150mm axial extract fan suitable for kitchen and utility rooms.

Key Features

- SFP down 0.28W/l/s
- Suitable for wall or ceiling mounting
- High Quality ABS moulding with external gloss finish
- Quiet Operation
- Comes complete with backdraught shutter

Technical Specification

Meets the requirements of Building Regulation Document F and L.

IP44 rated and CE marked in accordance with all the relevant EEC Harmonised Directives.

Double Insulated, class II motor fitted with thermal protection

Airflow: 230.4m³/hr

Specific Fan Power (SFP) Requirements

1.0 a. Mechanical ventilation systems should be designed to minimise electric fan power. Specific fan power (SFP) should not be worse than:

- i. 0.5 Watts per litres per seconds for intermittent extract ventilation systems
- ii. 0.7 Watts per litres per seconds for continuous extract ventilation systems
- iii. 1.5 Watts per litres per seconds for continuous supply and extract with heat recovery ventilation systems.

Product Range Details

Rated Voltage 220-240v-50Hz

Rated Wattage 18W

Noise Level 40dB(A)

Max. Operating Temp. 40°C

Max. Pressure 50p.a.

Hole Dimension (Wall) 173mm

Dimensions

Height

-

205mm

Width

-

205mm

Depth

-

110mm

Source URL: <http://www.anda.co.uk/products/ventilation/150mm-axial-fan-part-l-compliant>