

150mm Axial Fan with Pull Cord and Shutters



[Operations & Maintenance Manual \(pdf\)](#)

[Web Page \(pdf\)](#)

Model: 406108

Axial extract fan with pull cord backdraught shutter. Suitable for panel mounting or wall/window mounting using the appropriate accessory kit.

Key Features

- Suitable for panel, wall or window mounting
- All non pull-cord variants can be ceiling mounted
- High quality ABS mouldings with external gloss finish
- Quiet Operation
- Reversible grommet for surface of flush mounting

Technical Specification

- Meets the requirements of Building Regulation Document F
- IP22 rated, BEAB Approved, and CE marked in accordance with all the relevant EEC Harmonised Directives
- Double Insulated, class II motor fitted with thermal protection

- Hole Diameters: Window 160mm, Wall 170mm
- Airflow: Panel Mount 245m³/hr, Window/Wall 220³m/hr

Product Range Details

- Rated Voltage 220-240v-50Hz
- Rated Wattage 25W

Accessories

- Window Kit
- Wall Kit
- External wall grille
- External gravity wall grille
- Ducting

Dimensions

Height

-

225mm

Width

-

218mm

Depth

-

119mm

Source URL:

<http://www.anda.co.uk/products/ventilation/150mm-axial-fan-pull-cord-and-shutters>