

150mm Mixed Flow Fan



Download



[Web Page \(pdf\)](#)

Model: 477635

150mm mixed flow high performance extract fan suitable for use in restricted spaces such as ceiling restricted spaces such as ceiling voids traditionally found in refurbishments.

Key Features

- Integral foot plate provides secure, fast mounting
- Spigot designed for speedy installation of flexible ducting.
- Mixed flow fans develop greater pressure than conventional axial fans making them ideal for use in ducted systems
- 3 Speed fan setting

Technical Specification

- Fully Building Code Compliant
- IPX4 rated CE marked in accordance with all the relevant EEC Harmonised Directives
- Double Insulated with motor fitted with Thermal Protection

Performance

- High Speed: 855m³/h
- Low Speed: 400m³/h

Product Range Details

- Rated Voltage 220-240v-50Hz
- High Rated Wattage 120W
- Low Rated Wattage 42W
- High Speed Noise Level: 48dB(A) @ 3m
- Low Speed Noise Level 31dB(A) @ 3m

Accessories

- Wall Kit
- External wall grille
- Flexible Ducting
- Diameter of spigot: 98mm

Dimensions

Height

-

252mm

Width

-

226mm

Depth

-

307mm

Source URL: <http://www.anda.co.uk/products/ventilation/150mm-mixed-flow-fan>