

150mm Shower Fan and Light Kit with Timer Part L



Download



[Operations & Maintenance Manual \(pdf\)](#)

[Web Page \(pdf\)](#)

Model: 446682

This powerful 150mm in-line shower fan and light kit with timer, is designed for the safe ventilation of bathrooms, toilets and shower rooms by removing any risk of an electric shock in wet areas as the fan is mounted remotely.

Key Features

- SFP down to 0.31W/l/s
- Incorporates an integral adjustable electronic timer (1-20 mins)
- Quiet Operation
- Limited to 1.5mtrs of ducting when connected to an axial fan

Technical Specification

Meets the requirements of Building Regulation Document F and L.

IP44 rated.

CE marked in accordance with all the relevant EEC Harmonised Directives.

Double Insulated, class II

t: 01293 441690 e: info@anda.co.uk | sales@anda.co.uk | [Privacy & Cookies Policy](#)

Motor fitted with thermal protection

Airflow: Maximum 63 lts/sec

Specific Fan Power (SFP) Requirements

1.0 a. Mechanical ventilation systems should be designed to minimise electric fan

Fan Power power. Specific fan power (SFP) should not be worse than:

- i. 0.5 Watts per litres per seconds for intermittent extract ventilation systems
- ii. 0.7 Watts per litres per seconds for continuous extract ventilation systems
- iii. 1.5 Watts per litres per seconds for continuous supply and extract with heat recovery ventilation systems

Product Range Details

Rated Voltage 220-240v-50Hz

Maximum Pressure – 50Pa

Rated Wattage- 20.2watts

Sound Volume- 40dB(A)

Max Operating Temp – 40deg.C

Kit Comprises of the following:-

In Line 150mm shower fan

White/Chrome fitting Shower Light and fitting.

12 Volt Transformer

1.5mtrs PVC Ducting

Butterfly clips, cable ties and screw plugs

External Grille

Source URL:

<http://www.anda.co.uk/products/ventilation/150mm-shower-fan-and-light-kit-timer-part-l>