

150mm Standard Slim Axial Fan with Timer and Shutters



[Operations & Maintenance Manual \(pdf\)](#)

[Web Page \(pdf\)](#)

Model: 435962

Slim axial extract fan with backdraught shutter and electronic overrun timer adjustable from 3 minute to 25 minutes, the factory setting is 15 minutes. Suitable for panel mounting or wall mounting using the appropriate accessory kit.

Key Features

- Slim, only 15mm thick
- Wall or ceiling mounting
- High quality ABS mouldings with external gloss finish
- Quiet Operation

Technical Specification

- Meets the requirements of Building Regulation Document F
- IP44 rated, GS Approved, and CE marked in accordance with all the relevant EEC Harmonised Directives
- Double Insulated, class II motor fitted with thermal protection

- Hole Diameters: Wall 155mm
- Airflow: Panel Mount 216m³/hr

Product Range Details

- Rated Voltage 220-240v-50Hz
- Rated Wattage 20W
- 45dBA @ 3m

Accessories

- Wall Kit
- External wall grille
- External gravity wall grille
- Ducting

Dimensions

Height

-

225mm

Width

-

225mm

Depth

-

15mm

Source URL:

<http://www.anda.co.uk/products/ventilation/150mm-standard-slim-axial-fan-timer-and-shutters>