

100mm Axial Fan with Timer



[Operations & Maintenance Manual \(pdf\)](#)

[Web Page \(pdf\)](#)

Model: 457086

Axial extract fan with adjustable electronic overrun timer (the factory setting is 15 min). Suitable for panel mounting or wall/window mounting using the appropriate accessory kit.

Key Features

- Wall or ceiling mounting
- All non pull-cord variants can be ceiling mounted
- High quality ABS mouldings
- With external gloss finish
- Quiet Operation

Technical Specification

- Meets the requirements of Building Regulation Document F.
- IP44 rated, BEAB Approved, and CE marked in accordance with all the relevant EEC Harmonised Directives.
- Double Insulated, class II motor fitted with thermal

100mm Axial Fan with Timer

Published on Anda Products (<https://www.anda.co.uk>)

protection

- Hole Diameters: Window 105mm, Wall 115mm
- Airflow: Panel Mount 88m³/hr, Window/Wall 54m³/hr

Product Range Details

- Rated Voltage 220-240v-50Hz
- Rated Wattage 16W
- Motor speed 2100rpm
- Noise Level 30dB(A)

Accessories

- Window Kit
- Wall Kit
- External wall grille
- External gravity wall grille
- External gravity grille
- Ducting

Dimensions

Height

-

154mm

Width

-

154mm

Depth

-

47mm

Source URL: <https://www.anda.co.uk/products/ventilation/100mm-axial-fan-timer>