

## 100mm Shower Fan and Light Kit with Timer Part L



Download



[Operations & Maintenance Manual \(pdf\)](#)

[Web Page \(pdf\)](#)

**Model: 446681**

100mm timer in line fan shower fan and light kit designed for the safe ventilation of bathrooms, toilets and shower rooms by removing any risk of an electric shock in wet areas as the fan is mounted remotely.

### Key Features

- SFP down to 0.43W/l/s
- Incorporates an integral adjustable electronic timer (1-20 mins)
- Quiet Operation
- Limited to 1.5mtrs of ducting when connected to an axial fan

### Technical Specification

Meets the requirements of Building Regulation Document F and L.

IP44 rated.

CE marked in accordance with all the relevant EEC Harmonised Directives.

Double Insulated, class II

## 100mm Shower Fan and Light Kit with Timer Part L

Published on Anda Products (<https://www.anda.co.uk>)

Motor fitted with thermal protection

Airflow: Maximum 24 lts/sec

### Specific Fan Power (SFP) Requirements

1.0 a. Mechanical ventilation systems should be designed to minimise electric fan

Fan Power power. Specific fan power (SFP) should not be worse than:

i. 0.5 Watts per litres per seconds for intermittent extract ventilation systems

ii. 0.7 Watts per litres per seconds for continuous extract ventilation systems

iii. 1.5 Watts per litres per seconds for continuous supply and extract with heat recovery ventilation systems

### Product Range Details

Rated Voltage 220-240v-50Hz

Maximum Pressure – 20Pa

Rated Wattage- 10.4watts

Sound Volume- 41dB(A)

Max Operating Temp – 40deg.C

### Source URL:

<https://www.anda.co.uk/products/ventilation/100mm-shower-fan-and-light-kit-timer-part-l>