

150mm Standard Slim Axial Fan with Integral Shutters



[Operations & Maintenance Manual \(pdf\)](#)

[Web Page \(pdf\)](#)

Model: 435961

Slim axial extract fan with integral backdraught shutters. Suitable for panel mounting or wall mounting using the appropriate accessory kit.

Key Features

- Slim, only 15mm thick
- Wall or ceiling mounting
- High quality ABS mouldings with external gloss finish
- Quiet Operation

Technical Specification

- Meets the requirements of Building Regulation Document F
- IP44 rated, GS Approved, and CE marked in accordance with all the relevant EEC Harmonised Directives
- Double Insulated, class II motor fitted with thermal protection
- Hole Diameters: Wall 155mm

150mm Standard Slim Axial Fan with Integral Shutters

Published on Anda Products (<https://www.anda.co.uk>)

- Airflow: Panel Mount 216m³/hr

Product Range Details

- Rated Voltage 220-240v-50Hz
- Rated Wattage 20W
- 45dBA @ 3m

Accessories

- Wall Kit
- External wall grille
- External gravity wall grille
- Ducting

Dimensions

Height

-

225mm

Width

-

225mm

Depth

-

15mm

Source URL:

<https://www.anda.co.uk/products/ventilation/150mm-standard-slim-axial-fan-integral-shutters>