



# 100mm Centrifugal Fan with Timer and Humidistat Part L Compliant (401082)

## Description

### Model: 401082

100mm centrifugal fan fitted with integral back draft shutters and humidistat 20-90%RH, adjustable electronic overrun timer (1?20 minutes) and pullcord over ride switch. Designed for ducted ventilation of internal toilets, cloakrooms, bathrooms and shower rooms.

## Key Features

- Wall or Ceiling Mounting
- Suitable for wall or ceiling mounting
- High Impact ABS mouldings with external gloss finish
- Integral Backdraught Shutter
- Long Life Motor
- Flush or Surface Mountable
- Adjustable 98mm rear or side exit spigot

## Technical Specification

- Meets the requirements of Building Regulation Document F
- IP44 rated, BEAB Approved, and CE marked in accordance with all the relevant EEC Harmonised Directives
- Double Insulated, class II motor fitted with thermal protection
- Hole Diameters: Wall 117mm
- Airflow: 75m<sup>3</sup>/hr

## Product Range Details

- Rated Voltage 220-240v-50Hz
- Rated Wattage 11W

- Noise Level 36dB(A)

## **Accessories**

- Wall Kit
- External wall grille
- Flexible Ducting

## **Dimensions**

Height – 256mm

Width – 210mm

Depth – 100mm