



# 100mm SELV Low Profile Axial Fan with Timer and Backdraught Shutter (405677)

# **Description**

Model: 405677

Slim axial extract fan with backdraught shutter and electronic overrun timer adjustable from 1 minute to 30 minutes, the factory setting is 15 minutes. SELV 12V AC. Suitable for panel mounting or wall mounting by using the appropriate accessory kit.

## **Key Features**

- SELV (Safety Extra Low Voltage)
- Slim â?? only 15mm thick
- · Suitable for wall or ceiling mounting
- High Quality ABS mouldings with external gloss finish
- Quiet Operation
- Adjustable overrun timer
- Backdraught shutter

#### **Technical Specification**

- Meets the installed performance requirements of Building Regulations Document F for a wall fan
- IPX7 fan suitable for installing in zone 1. GS approved and CE marked in accordance with all the relevant EEC Harmonised Directives
- Double Insulated, class III motor fitted with thermal protection, controller class II
- Hole Diameters: ?115mm
- Airflow: Panel Mount 90mÂ<sup>3</sup>/hr

#### **Product Range Details**

Rated Voltage 220-240v-50Hz



- Rated Wattage 23W
- Noise Level 37.8dB(A)

## **Accessories**

- Wall Kit
- External wall grille
- External gravity grille
- Ducting

## **SELV Transformer Dimensions**

Height: 86mm Width: 147mm Depth: 66mm

#### **Dimensions**

Height â?? 159mm Width â?? 159mm Depth â?? 15mm