



# 100mm Timer Axial Fan Part L Compliant (446674)

### **Description**

Model: 446674

100mm axial extract fan with adjustable timer (1-20 mins) designed to meet the new Part L building regulations, for use in bathrooms and toilets.

#### **Key Features**

- SFP down 0.42W/l/s
- Suitable for wall or ceiling mounting
- · High Quality ABS moulding with external gloss finish
- Quiet Operation
- · Comes complete with backdraught shutter

#### **Technical Specification**

- Meets the requirements of Building Regulation Document F and L
- IP44 rated and CE marked in accordance with all the relevant EEC Harmonised Directives
- Double Insulated, class II motor fitted with thermal protection
- Airflow: 91.8m³/hr

## Specific Fan Power (SFP) Requirements

Mechanical ventilation systems should be designed to minimise electric fan power. Specific fan power (SFP) should not be worse than:

- i. 0.5 Watts per litres per seconds for intermittent extract ventilation systems
- ii. 0.7 Watts per litres per seconds for continuous extract ventilation systems
- iii. 1.5 Watts per litres per seconds for continuous supply and extract with heat recovery ventilation systems



# **Product Range Details**

- Rated Voltage 220-240v-50Hz
- Rated Wattage 10.77W
- Motor speed 2400rpm
- Noise Level 41dB(A)
- Max. Operating Temp. 40 degrees celcius
- Max. Pressure 20p.a.

#### **Dimensions**

Height â?? 205mm Width â?? 205mm Depth â?? 110mm