



## 150mm Axial Fan with timer and Shutters (426568)

### Description

#### Model: 426568

Axial extract fan with backdraught shutter and electronic overrun timer adjustable from 1 minute to 25 minutes, the factory setting is 15 minutes. Suitable for panel mounting or wall/window mounting using the appropriate accessory kit.

### Key Features

- Suitable for panel, wall or window mounting.
- All non pull-cord variants can be ceiling mounted
- High quality ABS mouldings with external gloss finish
- Quiet Operation
- Reversible grommet for surface of flush mounting.

### Technical Specification

- Meets the requirements of Building Regulation Document F
- IP22 rated, BEAB Approved, and CE marked in accordance with all the relevant EEC Harmonised Directives
- Double Insulated, class II motor fitted with thermal protection
- Hole Diameters: Window 160mm, Wall 170mm
- Airflow: Panel Mount 245m<sup>3</sup>/hr, Window/Wall 220m<sup>3</sup>/hr

### Product Range Details

- Rated Voltage 220-240v-50Hz
- Rated Wattage 25W

### Accessories

- Window Kit

- Wall Kit
- External wall grille
- External gravity wall grille
- Ducting

## **Dimensions**

Height â?? 225mm

Width â?? 218mm

Depth â?? 119mm