



150mm Axial Fan with Timer, Humidistat and Shutters (426569)

Description

Model: 426569

Axial extract fan with integral humidity controller, backdraught shutter and a direct switching override at low humidities. The humidity setting is adjustable 60%RH to 90%RH at a normal 20 degrees celcius, the factory setting is 75%RH. Suitable for panel mounting or wall/window mounting using the appropriate accessory kit.

Key Features

- Suitable for panel, wall or window mounting.
- All non pull-cord variants can be ceiling mounted
- High quality ABS mouldings with external gloss finish
- Quiet Operation
- Reversible grommet for surface of flush mounting.

Technical Specification

- Meets the requirements of Building Regulation Document F
- IP22 rated, BEAB Approved, and CE marked in accordance with all the relevant EEC Harmonised Directives
- Double Insulated, class II motor fitted with thermal protection
- Hole Diameters: Window 160mm, Wall 170mm
- Airflow: Panel Mount 245m³/hr, Window/Wall 220³m/hr

Product Range Details

- Rated Voltage 220-240v-50Hz
- Rated Wattage 25W

Accessories

- Window Kit
- Wall Kit
- External wall grille
- External gravity wall grille
- Ducting

Dimensions

Height – 225mm

Width – 218mm

Depth – 119mm