



## 150mm Axial Fan with Timer, Humidistat and Shutters (426569)

### Description

#### Model: 426569

Axial extract fan with integral humidity controller, backdraught shutter and a direct switching override at low humidities. The humidity setting is adjustable 60%RH to 90%RH at a normal 20 degrees celcius, the factory setting is 75%RH. Suitable for panel mounting or wall/window mounting using the appropriate accessory kit.

### Key Features

- Suitable for panel, wall or window mounting.
- All non pull-cord variants can be ceiling mounted
- High quality ABS mouldings with external gloss finish
- Quiet Operation
- Reversible grommet for surface of flush mounting.

### Technical Specification

- Meets the requirements of Building Regulation Document F
- IP22 rated, BEAB Approved, and CE marked in accordance with all the relevant EEC Harmonised Directives
- Double Insulated, class II motor fitted with thermal protection
- Hole Diameters: Window 160mm, Wall 170mm
- Airflow: Panel Mount 245m<sup>3</sup>/hr, Window/Wall 220m<sup>3</sup>/hr

### Product Range Details

- Rated Voltage 220-240v-50Hz
- Rated Wattage 25W

## Accessories

- Window Kit
- Wall Kit
- External wall grille
- External gravity wall grille
- Ducting

## Dimensions

Height â?? 225mm

Width â?? 218mm

Depth â?? 119mm