



150mm with Timer Axial Fan Part L Compliant (446677)

Description

Model: 446677

150mm axial extract fan suitable for kitchen and utility rooms. This model incorporates an adjustable electronic timer (1-20mins)

Key Features

- SFP down 0.28W/l/s
- Suitable for wall or ceiling mounting
- High Quality ABS moulding with external gloss finish
- Quiet Operation
- Comes complete with backdraught shutter
- Limited to 1.5mtrs of ducting when connected to an axial fan.

Technical Specification

Meets the requirements of Building Regulation Document F and L.

IP44 rated and CE marked in accordance with all the relevant EEC Harmonised Directives.

Double Insulated, class II motor fitted with thermal protection

Airflow: 64l/s

Specific Fan Power (SFP) Requirements

1.0 a. Mechanical ventilation systems should be designed to minimise electric fan power. Specific fan power (SFP) should not be worse than:

- 0.5 Watts per litres per seconds for intermittent extract ventilation systems
- 0.7 Watts per litres per seconds for continuous extract ventilation systems
- 1.5 Watts per litres per seconds for continuous supply and extract with heat recovery ventilation

systems.

Product Range Details

Rated Voltage 220-240v-50Hz

Rated Wattage 18W

Noise Level 40dB(A)

Max. Operating Temp. 40 degrees celcius

Max. Pressure 50p.a.

Hole Dimension (Wall) 173mm

Dimensions

Height ??? 205mm

Width ??? 205mm

Depth ??? 45mm spigot depth